

**Declaration of Performance**No.
00836-CPD-537586

1. Product Group: Group – 13 – Roofing membranes with glass carrier, APP modified with sand surfacing and a sacrificial plastic film backing.

2. Unique Product Names / Codes:

Product Code	Product Name	Nominal Weight	Nominal Dimensions
10205566	FIX-R APP T-O Universal Underlay	2.0 kg/m ²	16 x 1m
10205594	FIX-R Classic T-O Universal Underlay	2.0 kg/m ²	16 x 1m
10537955	FIX-R Classic 3B	1.8 kg/m ²	20 x 1m

3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Applied as a multi-layer system by self-adhesion of the products, hot applied bitumen or by torching – refer to manufacturers technical Data Sheet.

4. Manufacturer: FIX-R, Harding Way, St Ives, Cambridgeshire, PE27 3YJ
www.fix-r.co.uk info@fix-r.co.uk

5. Authorised Representative: Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR: 2+

7. Harmonised standard: EN 13707:2004 +A2:2009

8. Notified Body: BSI – year of certification – 08

9. Declared Performance:

Essential Characteristic	Performance	Harmonised Technical Specification
External fire performance	F _{Roof} (t4)	EN 13501-5
Reaction to fire	F	EN 13501-1

Watertightness	Pass	EN 1928
Maximum tensile force	Long \geq 300 N/50mm Tran \geq 200 N/50mm	EN 12311-1
Elongation	Long \geq 2 % Tran \geq 2 %	EN 12311-1
Resistance to tearing	Long \geq 70 N Tran \geq 70 N	EN 12310-1
Flexibility at low temperature	Upper \leq -5°C Lower \leq -5°C	EN 1109

Signed on behalf of the manufacturer by:



Andrew Wakelin
Managing Director
SIG UK Exteriors
January 2017