

## **Declaration of Performance**

## **No.** 00836-CPD-537586



**1. Product Group:** Group – 16 – Roofing membranes with glass carrier, APP modified with sand surfacing and a

sacrificial plastic film backing.

## 2. Unique Product Names / Codes:

Product Code	Product Name	Nominal Weight	Nominal Dimensions
10205574	FIX-R APP Cap Brown	4.5 kg/m2	8 x 1m
10205575	FIX-R APP Cap Black	4.5 kg/m2	8 x 1m
10205576	FIX-R APP Cap Blue/Grey	4.5 kg/m2	8 x 1m
10205590	FIX-R Classic T-O Green	4.12 kg/m2	8 x 1m
10205591	FIX-R Classic T-O Black	4.12 kg/m2	8 x 1m
10205592	FIX-R Classic T-O Blue/Grey	4.12 kg/m2	8 x 1m
10205593	FIX-R Classic T-O Brown	4.12 kg/m2	8 x 1m

3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Applied as a multi-layer system by self-adhesion of the products, hot applied bitumen or by torching – refer to manufacturers technical Data Sheet.

4. Manufacturer: FIX-R, Harding Way, St Ives, Cambridgeshire, PE27 3YJ

www.fix-r.co.uk info@fix-r.co.uk

5. Authorised Representative: Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set

out in Annex V of the CPR: 2+

**7. Harmonised standard:** EN 13707:2004 +A2:2009

**8. Notified Body:** BSI – year of certification – 08

## 9. Declared Performance:

Essential Characteristic	Performance	Harmonised Technical Specification	
External fire performance	F <sub>Roof</sub> (t4)	EN 13501-5	
Reaction to fire	F	EN 13501-1	
Watertightness	Pass	EN 1928	
Maximum tensile force	Long ≥ 500 N/50mm Tran ≥ 300 N/50mm	EN 12311-1	
Elongation	Long ≥ 40 % Tran ≥ 40 %	EN 12311-1	
Resistance to tearing	Long ≥ 200 N Tran ≥ 200 N	EN 12310-1	
Flexibility at low temperature	Upper ≤ -5°C Lower ≤ -5°C	EN 1109	

Signed on behalf of the manufacturer by:

Andrew Wakelin Managing Director

SIG UK Exteriors

January 2017