

**Declaration of Performance**No.  
00836-CPD-537586

**1. Product Group:** Group – 6 – Roofing membranes with a polyester carrier, oxidised bitumen / SBS modified with sand surfacing and a sacrificial plastic film backing.

**2. Unique Product Names / Codes:**

| Product Code | Product Name                     | Nominal Weight        | Nominal Dimensions |
|--------------|----------------------------------|-----------------------|--------------------|
| 10205566     | FIX-R SBS T-O Universal Underlay | 2.2 kg/m <sup>2</sup> | 16 x 1m            |

**3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Applied as a multi-layer system by self-adhesion of the products, hot applied bitumen or by torching – refer to manufacturers technical Data Sheet.

**4. Manufacturer:** FIX-R, Harding Way, St Ives, Cambridgeshire, PE27 3YJ  
[www.fix-r.co.uk](http://www.fix-r.co.uk) [info@fix-r.co.uk](mailto:info@fix-r.co.uk)

**5. Authorised Representative:** Not applicable

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR:** 2+

**7. Harmonised standard:** EN 13707:2004 +A2:2009

**8. Notified Body:** BSI – year of certification - 08

**10. Declared Performance:**

| Essential Characteristic  | Performance            | Harmonised Technical Specification |
|---------------------------|------------------------|------------------------------------|
| External fire performance | F <sub>Roof</sub> (t4) | EN 13501-5                         |
| Reaction to fire          | F                      | EN 13501-1                         |
| Watertightness            | Pass                   | EN 1928                            |

Signed on behalf of the manufacturer by:

Andrew Wakelin  
Managing Director  
SIG UK Exteriors  
January 2017