


- 1. Fix-R EPDM Membrane
- 2. Reinforced Universal Secure Strip (RUSS)
- 3. Suitable Fastener with 50mm Seam Plates
- 4. Fix-R EPDM Decking Adhesive (Determined by deck type)
- 5. Fi-xR EPDM Bonding Adhesive
- 6. Suitable thermal insulation, thickness determined by U-value
- 7. Vapour Control Layer (VCL)
- 8. Structural decking
- 9. Treated timber by others

PS Cover Tape to seam angle change Note 2

Diagram 2

Notes:
 1. This detail was prepared to serve as a guideline representing typical detailing conditions and illustrate the correct application of Fix-R EPDM products only. It may be necessary to modify this detail in whole or part in accordance with specific project conditions, design or requirements.
 2. Acrylic Decking Adhesive is for timber substrates only, all other suitable surfaces use Fix-R EPDM Bonding Adhesive
 3. If 75mm field seam turns up through angle change install Pressure Sensitive cover tape using 225mm Uncured EPDM tape.
 4. Alternate fixing detail for RUSS as shown in diagram 2.

	Title BOX GUTTER		Drawn MFO		Checked DW		Approved DW		Scale 1: 4@A4		Date 03.02.14			
	Product CB-BG-1		Status PRODUCTION											
	A 03.02.14		Drawing No: CB/BG/1										Rev: A	
	Rev Date		Comments PRODUCTION Issue											