



Diagram 2

1. Fix-R EPDM Membrane
2. Fix-R EPDM Decking Adhesive
3. Fix-R EPDM Bonding Adhesive
4. Suitable thermal insulation, thickness determined by U-value
5. Vapour Control Layer (VCL)
6. Structural decking
7. Suitable cavity bridge
8. Thermal insulation to detailing where applicable
9. Prefabricated metal coping, by others
10. Reinforced Universal Secure Strip (RUSS)
11. Suitable Fastener with 50mm Seam Plates

Notes:

1. This detail was prepared to serve as a guideline representing typical detailing conditions and illustrate the correct application of Fix-R EPDM products only. It may be necessary to modify this detail in whole or part in accordance with specific project conditions, design or requirements.
2. Acrylic Decking Adhesive is for timber substrates only, all other suitable surfaces use Fix-R EPDM Bonding Adhesive.
3. Alternate fixing detail for RUSS as shown in diagram 2.



|                              |  |
|------------------------------|--|
| Title<br>METAL COPING DETAIL |  |
| Product<br>CB-W-4            |  |

|     |          |                  |
|-----|----------|------------------|
| A   | 03.02.14 | PRODUCTION Issue |
| Rev | Date     | Comments         |

|                       |         |          |         |           |
|-----------------------|---------|----------|---------|-----------|
| Drawn                 | Checked | Approved | Scale   | Date      |
| MFO                   | DW      | DW       | 1: 4@A4 | 03.02.14  |
| Status<br>PRODUCTION  |         |          |         |           |
| Drawing No:<br>CB/W/4 |         |          |         | Rev:<br>A |