



- 1. Fix-R EPDM Membrane
- 2. Fix-R EPDM Decking Adhesive (See Notes)
- 3. Fix-R EPDM Bonding Adhesive
- 4. 150mm PS Cover Strip
- 5. Suitable thermal insulation, thickness determined by U-value
- 6. Vapour Control Layer (VCL)
- 7. Structural decking
- 8. Prefabricated metal edge trim @ 300mm max centres
- 9. Pitched roof underlay
- 10. Roof tile (by others)
- 11. Lead flashing (by others)
- 12. Sure Edge front plate
- 13. Sure Edge standard back plate
- 14. Reinforced Universal Secure Strip (RUSS)
- 15. Suitable Fastener with 50mm Seam Plate

Notes:  
 1. This detail was prepared to serve as a guideline representing typical detailing conditions and illustrate the correct application of Fix-R EPDM products only. It may be necessary to modify this detail in whole or part in accordance with specific project conditions, design or requirements.  
 2. Acrylic Decking Adhesive is for timber substrates only, all other suitable surfaces use Fix-R EPDM Bonding Adhesive.  
 3. Spacings for fixings may need to be reduced to 150mm centres dependant on location & climatic conditions.  
 4. Diagram 2 shows use of alternate detail using SureEdge PVC drip trim.



|   |  |
|---|--|
| Title<br>FLAT ROOF TO PITCH ROOF<br>TERMINATION (MANSARD) |  |
| Product<br>CB-T-2   |  |

|     |          |                  |
|-----|----------|------------------|
| A   | 03.02.14 | PRODUCTION Issue |
| Rev | Date     | Comments         |

|                       |         |            |         |           |
|-----------------------|---------|------------|---------|-----------|
| Drawn                 | Checked | Approved   | Scale   | Date      |
| MFO                   | DW      | DW         | 1: 4@A4 | 03.02.14  |
| Status                |         | PRODUCTION |         |           |
| Drawing No:<br>CB/T/2 |         |            |         | Rev:<br>A |