



1. Fix-R EPDM Membrane
2. Fix-R EPDM Decking Adhesive (See Notes)
3. 150mm PS Cover Strip
4. Suitable thermal insulation, thickness determined by U-value
5. Vapour Control Layer (VCL)
6. Structural decking
7. Lead flashing (by others)
8. Pitched roof underlay
9. Roof tile (by others)

Notes:

1. This detail was prepared to serve as a guideline representing typical detailing conditions and illustrate the correct application of Fix-R EPDM products only. It may be necessary to modify this detail in whole or part in accordance with specific project conditions, design or requirements.
2. Acrylic Decking Adhesive is for timber substrates only, all other suitable surfaces use Fix-R EPDM Bonding Adhesive.
3. Spacings for fixings may need to be reduced to 150mm centres dependent on location & climatic conditions.



Title
FLAT ROOF TO PITCH ROOF LEAD
TERMINATION (MANSARD)

Product
CB-T-3

| | | |
|-----|----------|------------------|
| A | 03.02.14 | PRODUCTION Issue |
| Rev | Date | Comments |

| | | | | |
|-----------------------|---------|----------|---------|-----------|
| Drawn | Checked | Approved | Scale | Date |
| MFO | DW | DW | 1: 4@A4 | 03.02.14 |
| Status PRODUCTION | | | | |
| Drawing No: CB/T/3 | | | | Rev: A |