




PRODUCT DATA SHEET

FIX-R 20 SBS Modified Torch On Capsheet



Features & Benefits

- Torch on Application
- Strong polyester reinforcement
- Flexible SBS bitumen
- Low temperature flexibility - 15°C
- Cost effective performance
- 20 year Materials Guarantee

Description FIX-R 20 SBS T-O Capsheet is a non woven polyester based torch applied capsheet, coated with an SBS rubber modified bitumen coating. The upper surface is finished with mineral granules, and the lower surface has a torching film which is rapidly dispersed, making application fast and secure.

A 75mm selvedge facilitates bonding of side laps.

Product Details

Product	FIX-R 20 SBS T-O Capsheet
Roll Weight (kg)	40kg
Kg/m ²	5Kg/m ²
Roll Dimensions	8m x 1m
Base Type	Polyester

Colours

Green
Black



0086-CPD-537 586

Typical Properties

Property	Test Method	Unit	FIX-R 20 SBS T-O Capsheet
Tensile Strength	BSEN 12311-2000	N/50mm	MD >500 TD >400
Elongation at break	BSEN 12311-2000	%	MD >20 TD >30
Low Temperature Flexibility	BSEN 1109-2000	°C	≤ -15

Application

FIX-R 20 SBS T-O Capsheet waterproofing membrane is suitable for use as the uppermost layer of a built-up roofing system.

FIX-R 20 SBS T-O Capsheet waterproofing membrane should be installed in accordance with BS 8217:2005 Code of Practice for Reinforced Bitumen Membranes for roofing, and BS6229 Code of Practice for Flat Roofs with continuously supported roof coverings. The application should follow the recommended good practices for torch-applied membranes.

Apply **FIX-R 20 SBS T-O Capsheet** waterproofing membrane by melting the heat dispersible backing and coating to create a molten flow in front of the roll. The flame of the torch should be applied at the low point where the roll meets the underlay. As the film and bitumen melts, roll the roofing membrane forward. Side joints in the sheets should be fully bonded and formed using the 75mm selvedge, end laps should be a minimum of 100mm. NB. A bead of bitumen must exude from all side and end laps joints to ensure a seal.

Care must be taken when applying these torch-on membranes in close proximity to combustible materials, decorative coatings and heat sensitive materials.

Storage and handling

FIX-R 20 SBS T-O Capsheet membranes should be stored on end, on a clean level surface away from excessive heat and under cover.



Other Literature

Full product literature, Health & Safety documentation (where applicable) and any further documented literature is available from our website www.fix-r.co.uk or on request by email to info@fix-r.co.uk.

FIX-R

Harding Way,
St Ives,
Cambridgeshire,
PE27 3YJ

Tel: 01480 466777
Fax: 01480 290133

Email: info@fix-r.co.uk
Web: www.fix-r.co.uk

This technical datasheet is applied to products sold by SIG Trading and valid until withdrawal or until modification. Since this datasheet may be subject to revision, it is the responsibility of designer/end-user to make sure of possessing the latest version of the datasheet (*see date of issuing). The most recent version of this datasheet can be also accessed under www.fix-r.co.uk. Modification of the technical datasheet repeals the previously issued versions.