

**Declaration of Performance**No.  
00836-CPD-537586

**1. Product Group:** Group – 14 – Roofing membranes with glass carrier, APP modified with sand surfacing and a sacrificial plastic film backing.

**2. Unique Product Names / Codes:**

Product Code	Product Name	Nominal Weight	Nominal Dimensions
10205577	FIX-R APP Sanded Top Layer	4.0 kg/m <sup>2</sup>	8 x 1m
10537954	FIX-R 180 Polyester Underlay	1.9 kg/m <sup>2</sup>	20 x 1m

**3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Applied as a multi-layer system by self-adhesion of the products, hot applied bitumen or by torching – refer to manufacturers technical Data Sheet.

**4. Manufacturer:** FIX-R, Harding Way, St Ives, Cambridgeshire, PE27 3YJ  
[www.fix-r.co.uk](http://www.fix-r.co.uk) [info@fix-r.co.uk](mailto:info@fix-r.co.uk)

**5. Authorised Representative:** Not applicable

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR:** 2+

**7. Harmonised standard:** EN 13707:2004 +A2:2009

**8. Notified Body:** BSI – year of certification – 08

**9. Declared Performance:**

Essential Characteristic	Performance	Harmonised Technical Specification
External fire performance	F <sub>Roof</sub> (t4)	EN 13501-5
Reaction to fire	F	EN 13501-1
Watertightness	Pass	EN 1928

Maximum tensile force	Long $\geq$ 500 N/50mm Tran $\geq$ 300 N/50mm	EN 12311-1
Elongation	Long $\geq$ 40 % Tran $\geq$ 40 %	EN 12311-1
Resistance to tearing	Long $\geq$ 200 N Tran $\geq$ 200 N	EN 12310-1
Flexibility at low temperature	Upper $\leq$ -5°C Lower $\leq$ -5°C	EN 1109

Signed on behalf of the manufacturer by:



Andrew Wakelin  
Managing Director  
SIG UK Exteriors  
January 2017