

# FIX-R

## FIX-R All Weather Roof Coat

**REJUVENATES YOUR ROOF**



**SEAMLESS WATERPROOF COATING  
TO PROLONG THE LIFE OF FLAT ROOFS.**

### **Description**

FIX-R All Weather Roof Coat is a flexible, bituminous coating containing reinforcing fibres and designed for easy application to protect and prolong the life of existing roofing systems.

The ideal solution for protecting and rejuvenating your roof.

## Directions for use

### Surface Preparation

All surfaces must be clean, dry and free from grease, oil, dirt and loose material. Destroy any moss or lichen growth using Algae and Fungi Remover and prime the surface being treated with FIX-R Quick Dry Bitumen Primer and allow to dry. Metal surfaces, where necessary, should be prepared with a wire brush.

Prime iron and steel with suitable rust inhibitive primer, and allow to dry thoroughly. Any blisters and cracks present in the existing roof surface should be repaired using a Universal Roof Repair Compound.

### Application

Stir FIX-R All Weather Roof Coat thoroughly and then apply an even coating using a brush at a rate of 2m<sup>2</sup>/litre. Allow product to dry thoroughly (approximately 24 hours) and then apply a second coat at right angles to the first at a rate of 2m<sup>2</sup>/litre. For additional ultraviolet protection, slate flakes or chippings can be immediately sprinkled onto the top coat whilst still wet.

### Coverage

2m<sup>2</sup> / litre / coat

### Cleaning

White Spirit

### Packaging

5L & 25L

### Storage

Containers should be kept sealed in a cool, dry, well ventilated environment and all practical precautions taken against fire. Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

### Shelf Life

Maximum 3 years in sealed container.

### Health & Safety

Keep away from sources of ignition, including pilot lights and sparks. No smoking. Avoid contact with skin by careful working and use of gloves. In case of contact with skin wash immediately with soap or a recognised skin cleanser. Do not use solvents to clean the skin. Use only in well ventilated areas. When using, do not eat, drink or smoke.

Do not empty into drains. Remove excess material from tools before cleaning. Some local authorities have special facilities for the disposal of waste liquids. Remove lid and allow residue to dry in a safe place prior to disposal of empty containers. A separate safety datasheet is available on request to FIX-R.

### Fire

In case of fire use foam, dry powder or CO<sub>2</sub> extinguisher, sand or earth. Never use water.



# FIX-R

Harding Way,  
St Ives,  
Cambridgeshire,  
PE27 3YJ

Tel: 01480 466777  
Fax: 01480 290133

Email: [info@fix-r.co.uk](mailto:info@fix-r.co.uk)

[www.fix-r.co.uk](http://www.fix-r.co.uk)