


# TAPE 10

# FIXER CLASSIC



**High adhesive butyl self adhesive tape protected by a polypropylene fleece.**

## **Description**

FIX-R Classic Tape 10 is a self-adhesive tape made of a butyl rubber compound protected by a fleece in polypropylene. The tape has been developed for applications where it is necessary to have a high adhesion property on materials like concrete, gypsum boards and marble.

FIX-R Classic Tape 10 is compatible with most common glues (cement and non-cement based adhesive) and it is ideal to be used under wood, marble, ceramic etc coverings (users own testing should be carried out to ensure compatibility).

Tape 10 is highly adhesive to all materials and especially to plastic, glass, steel, polycarbonate, wood and bitumen.

### **Recommended For**

The product is designed to seal and reinforce the joints between timber decks, roof sheets and approved insulation boards prior to the application of the FIX-R Classic Liquid 10 system.

All surfaces must be primed using FIX-R Classic Primer 10 and allowed to fully cure before tape application.

### **Features & Benefits**

- ◆ Excellent adhesive properties
- ◆ Excellent heat stability
- ◆ Excellent adhesion at low temperatures
- ◆ High workability, plasticity and formability
- ◆ Solvent free

### **Application Prerequisites**

Tape 10 is compatible with most building materials, metals and flexible or hard plastics. The surface should be clean, dry, smooth and dust-free. If the installation surface is porous a primer will have to be applied.

### **Application Procedure**

Prepare the surface and proceed as follows:

1. Ensure the surface area to be bonded is solid, dry, clean and free from grease.
2. Cut tape to the required size and peel backing paper from the beginning of the roll.
3. Adhere the first section of tape to the beginning of the joint, applying pressure (ideally with a roller) to the tape as it makes contact with the substrate to ensure 100% adhesion between the substrate and tape.
4. Continue along the joint, removing the backing paper as required, ensuring that the tape is applied in a straight line.
5. Ensure an overlap of 50mm between tape joints as required.
6. Apply FIX-R Classic Liquid 10 as per Installation Guidelines.

### **Packaging**

- ◆ Standard length: 10 meters
- ◆ Standard width: 75mm

### **Shelf Life**

Can be kept indefinitely in a dry, cool environment.

### **Safety Information**

The material is not hazardous for normal uses and when used by skilled persons. Keep out of reach of children.

## Technical specification

PROPERTY	UNITS	METHOD	SPECIFICATION
Standard Thickness	mm		1.0
Colour			Grey
Tensile Strength	N/50mm	EN12311-1	Long>100, Trasv>100
Elongation at break		EN12311-1	Long>70%, Trasv>70%
Solids			100%
Specific Weight	g/cm <sup>3</sup>	ASTM D 792	1.4
Peel Adhesion 90o	N	ASTM D 1000	≥90
Loop Tack Test	N	ASTM D 6195	≥80
Probe Tack Test	N	ASTM D 2979	≥80
Vertical Flow	Mm	ISO 7390	0
Cement Adhesive Strength C2E on Fleece	N/mm <sup>2</sup>	EN 12004-EN1348	0.9
Application Temperature	°C		0 to 40
Service Temperature	°C		-30 to +80. Up to 160 for max 24hr

Certified quality, environmental and occupational health & safety management systems:  
ISO 9001/14001 & OHSAS 18001.

The logo for FIXER CLASSIC is displayed on a yellow diamond background. The word "FIXER" is in a bold, black, sans-serif font, and "CLASSIC" is in a larger, bold, grey, sans-serif font with a black outline.

Harding Way, St Ives, Cambridgeshire, PE27 3YJ  
Tel: 01480 466 777 Fax: 01480 290 133  
Email: [info@fix-r.co.uk](mailto:info@fix-r.co.uk) Website: [www.fix-r.co.uk](http://www.fix-r.co.uk)