

**PRODUCT DATA SHEET**

# Gutter Trim - Built in Batten

**Features & Benefits**

- **Unique 25mm thick Batten Back Plate, removing the need for additional timber batten**
- **Bevelled edge on back plate to ensure easy alignment of the front plate**
- **75mm deep front plate with compression sealing foam along the top edge to create a water tight seal to the membrane, over seams and detailing joints**
- **Pre-drilled fixing holes, for accurate and fast installation of the front plate**
- **Complete range of colour matched joints and corner accessories.**

**Description**


FIX-R Gutter Trim - Built in Batten gutter trim simplifies your gutter drip installation by removing the requirement of having to install a timber batten to the fascia board to create the step into the gutter. This is a two part trim, the batten back plate and the front plate, with compression seal along the top edge. Both sections are manufactured from co-extruded u-PVC creating a hard wearing, durable product.

**Intended  
Uses**

For creating a gutter drip edge to flat and low sloping roofs with FIX-R EPDM membrane.

**Installation**

- 1) Fix the Batten Back Plate to the face of the fascia ensuring the top edge is level with the top of the decking. Ensure that a 1mm expansion gap is left between lengths for each metre of trim used.
- 2) Dress the membrane down the face of the back plate. For best results bond the membrane to the top and front of the back plate.
- 3) Position the front plate onto the rubber so the sealant foam is compressed by 30% and the top edge of the front plate is below the level of the membrane.
- 4) Using the 65mm PolyTop nails fix the front plate into position. A fixing must be in each pre-drilled hole to achieve full compression.
- 5) Position the next length of front plate leaving a 1mm expansion gap for each metre of trim used.
- 6) Trim the excess membrane off below the back plate.
- 7) Fit the cover clips at each joint between lengths of trim.



#### Typical Properties & Characteristics

<b>Material</b>	<b>Co-extruded u-PVC</b>
<b>Colour</b>	<b>Black or white</b>
<b>Trim Length</b>	<b>2.5m</b>
<b>Additional Components</b>	<b>Trim Joints, Internal Corners, External Corners</b>



Harding Way,  
St Ives,  
Cambridgeshire,  
PE27 3YJ

Tel: 01480 466777  
Fax: 01480 290133

Email: [info@fix-r.co.uk](mailto:info@fix-r.co.uk)  
Web: [www.fix-r.co.uk](http://www.fix-r.co.uk)