



PRODUCT DATA SHEET

Stain Blocker

For use with FIX-R Liquid Waterproofing System

A highly penetrating, cost effective acrylic stain blocker

FIX-R Stain Blocker

- A low viscosity, highly penetrating, advanced acrylic polymer stain blocker.
- **FIX-R Stain Blocker** blocks the migration of asphaltic oils eliminating the risk of bleed through.
- If the substrate is in poor condition and showing signs of potential leaching, apply a coat of **FIX-R Stain Blocker**.
- All chippings or ballast must be removed from the substrate; the surface must be cleaned thoroughly by power washing and then sealed with **FIX-R Stain Blocker**.

Application

- Surfaces must be clean and dry, free of dirt, dust, loose granules, pollution fallout or other contamination.
- Thoroughly mix containers to achieve an even consistency prior to use.
- Apply with brush or roller.
- Apply **FIX-R Stain Blocker** at the rate of approximately 0.2L/m².
- Substrate porosity and texture will influence the coverage rate.
- Allow **FIX-R Stain Blocker** to dry thoroughly prior to applying **FIX-R Liquid Waterproofing**.

Typical Properties

- | | |
|--------------------|--------|
| • Tensile strength | 300psi |
| • Elongation | 500% |
| • Drying time | 1 hour |

Bucket Size

- 10 Litre plastic buckets.

Precautions

- **FIX-R Stain Blocker** will freeze and become unusable at temperatures below 0°C.
- Do not apply if weather conditions will not allow the **FIX-R Stain Blocker** to dry before rain, dew or freezing temperatures occur.
- For additional information refer to the SDS.
- Avoid contact with eyes and mucous membranes.
- If material comes in direct contact with skin, wash immediately with soap and water.

Safety & Handling

For specific information regarding safe handling of this material please refer to the Safety Data Sheet (SDS).