

FIBRED 10

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name FIX-R Classic Fibred 10
Stock codes K8 = 10513507
 Distributer code = 125550010

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use Novel, all weather rapid curing, single component polyurethane liquid membrane for waterproofing and protection based on Humidity-Activated-Accelerator, Technology <<FOR PROFESSIONAL USERS ONLY>>

1.3. Details of the supplier of the safety data sheet

Company identification SIG Roofing
 Harding Way, St Ives
 Cambridgeshire PE27 3YJ
 Tel: 01480 466 777

1.4. Emergency telephone number

01480 466 777



2. Hazards identification

2.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification : R10
 Xn; R20/21
 R43

Hazard Class and Category Code Regulation EC 1272/2008 (CLP)

Health hazards : Acute toxicity, Inhalation - Category 4 - Warning (CLP : Acute Tox. 4) H332
 Skin irritation - Category 2 - Warning (CLP : Skin Irrit. 2) H315
 Eye irritation - Category 2A - Warning (CLP : Eye Irrit. 2) H319
 Skin sensitisation - Category 1 - Warning (CLP : Skin Sens. 1) H317
 Specific Target Organ Toxicity - Repeated exposure - Category 2 - Warning (CLP : STOT RE 2) H373
Physical hazards : Flammable liquids - Category 3 - Warning (CLP : Flam. Liq. 3) H226

2.2. Label elements

Labelling EC 67/548 or EC 1999/45

Symbol(s)



Symbol(s) : Xn : Harmful
R Phrase(s) : R10 : Flammable.
 R20/21 : Harmful by inhalation and in contact with skin.
 R43 : May cause sensitization by skin contact.

2. Hazards identification (continued)

S Phrase(s)	: S2 : Keep out of the reach of children. S23 : Do not breathe the gas, fumes, vapours, spray. S24 : Avoid contact with skin. S36/37 : Wear suitable protective clothing and gloves. S40 : To clean the floor and all objects contaminated by this material, use xylene. S46 : If swallowed seek medical advice immediately and show this container or label. S51 : Use only in well-ventilated areas.
Contains	: Xylene - 1,6-hexanediy-l-bis (2-(2-(1-ethylpentyl)-3-oxazolidinyl) ethyl) carbamate << Contains isocyanates. See information supplied by the manufacturer>>.

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms



Signal words	: Warning
Hazard statements	: H226 : Flammable liquid and vapour. H319 : Causes serious eye irritation. H315 : Causes skin irritation. H317 : May cause an allergic skin reaction. H332 : Harmful if inhaled. H373 : May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

General	: P101 : If medical advice is needed, have product container or label at hand. P102 : Keep out of reach of children. P103 : Read label before use.
Prevention	: P280 : Wear eye protection, face protection. P280 : Wear protective gloves, protective clothing, eye protection, face protection. P210 : Keep away from heat, sparks, open flames or hot surfaces – No smoking. P233 : Keep container tightly closed. P240 : Ground/bond container and receiving equipment. P241 : Use explosion-proof electrical, ventilating, lighting, ..., equipment. P260 : Do not breathe dust, fume, gas, mist, vapours, spray. P264 : Wash thoroughly after handling. P271 : Use only outdoors or in a well-ventilated area. P272 : Contaminated work clothing should not be allowed out of the workplace.
Response	: P321 : Specific treatment (see on this label). P305+P351+P338: IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P370+P378: In case of fire: Use all extinguishing media for extinction. P304+P340: IF INHALED : Remove to fresh air and keep at rest in a position comfortable for breathing. P302+P352: IF ON SKIN : Wash with plenty of soap and water. P303+P361+P353: IF ON SKIN (or hair) : Remove immediately all contaminated clothing. Rinse skin with water/shower. P312: Call a POISON CENTER or doctor if you feel unwell. P333+P313 : If skin irritation or rash occurs : Get medical advice. P363 : Wash contaminated clothing before reuse.

2. Hazards identification (continued)

Storage : P403+P235 : Store in well-ventilated place. Keep cool.
Disposal considerations : P501 : Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Contains : Xylene - 1,6-hexanediy-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl) carbamate
Contains : EUH204: Contains isocyanates. May produce an allergic reaction

2.3. Other hazards

The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

3. Composition/information on ingredients

Substance / Preparation : Preparation.
Hazardous component(s) : This product is hazardous.

Substance name	Contents	CAS No	EC No	Annex No	REACH Ref.	Classification
Xylene	: <= 13.5	1330-20-7	215-535-7	601-022-00-9	----	R10 Xn; R20/21-65 Xi; R36/37/38 ----- Asp. Tox 1 _ H304 Flam. Liq. 3 _ H226 Acute Tox. 4 (skin) _ H312 Acute Tox. 4 (inhal) _ H332 Eye irrit 2 _ H319 Skin Irrit. 2 _ H315 STOT SE 3 _ H335 STOT RE 2 _ H373
1,6-hexanediy-bis (2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl) carbamate	: <= 2.5 %	140921-24-0	411-700-4	616-079-00-5	----	R43 ----- Skin Sens. 1 _ H317

4. First aid measures

4.1. Description of first aid measures

Inhalation : IF INHALED : Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor. Specific treatment is urgent.
Skin contact : IF ON SKIN : Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs : Get medical advice. Specific treatment.
Eye contact : If eye irritation persists : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Get medical advice.
Ingestion : Do not induce vomiting.
Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms relating to use : Causes serious eye irritation. Causes skin irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.

4.3. Indication of any immediate medical attention and special treatment needed

General information : Never give anything by mouth to an unconscious person.
If you feel unwell, seek medical advice (show the label where possible).

5. Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Water spray. Dry powder. Carbon dioxide. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

Surrounding fires : Use water spray or fog for cooling exposed containers.

5.2. Special hazards arising from the substance or mixture

Flammable class : Flammable liquid and vapour.

Hazardous combustion products : Under fire conditions, hazardous fumes will be present.

5.3. Advice for fire-fighters

Protection against fire : Do not enter fire area without proper protective equipment, including respiratory protection.

Special procedures : Exercise caution when fighting any chemical fire.
Avoid (reject) fire-fighting water to enter environment.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders : Equip cleanup crew with proper protection. Ventilate area.

Technical measures : Use special care to avoid static electric charges. Eliminate every possible source of ignition. No naked lights. No smoking.

Technical measures : Remove ignition sources. No naked lights. No smoking.

6.2. Environmental precautions

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean up methods : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spills and put it into appropriated container.

6.4. Reference to other sections

See section 8. Exposure controls/personal protection

7. Handling and storage

7.1. Precautions for safe handling

Technical protective measures : Use explosion-proof electrical, ventilating, lighting, ..., equipment. Use only non-sparking tools. Proper grounding procedures to avoid static electricity should be followed. Provide good ventilation in process area to prevent formation of vapour.

7. Handling and storage (continued)

Handling	: Wash thoroughly after handling. Wash thoroughly after handling. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Take precautionary measures against static discharge. Handle empty containers with care because residual vapours are flammable. Avoid breathing dust, fume, gas, mist, vapours, spray.
Special precautions	: No naked lights. No smoking. In use, may form flammable vapour-air mixture. Store and handle as though always a serious potential fire/explosion and health hazard exists. Avoid breathing dust, fume, gas, mist, vapours, spray.
7.2. Conditions for safe storage, including any incompatibilities	
Storage	: Ground/bond container and receiving equipment. Keep container tightly closed. Keep in fireproof place. Keep only in the original container in a cool, well ventilated place.
Storage - away from	: Heat sources. Direct sunlight, Strong bases. Strong acids. Sources of ignition.
7.3. Specific end use(s)	
Specific end use(s)	: None.

8. Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Personal protection



Personal protection

Respiratory protection

Hand protection

Skin protection

Eye protection

Others

- : Avoid all unnecessary exposure.
- : In case of insufficient ventilation, wear suitable respiratory equipment. Where excessive vapour may result, wear approved mask.
- : In case of repeated or prolonged contact wear gloves. Wear protective gloves.
- : Wear suitable protective clothing.
- : Chemical goggles or safety glasses.
- : When using, do not eat, drink or smoke.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: White
Odour	: Characteristic
Odour threshold	: No data available
pH value	: Not applicable
Melting point/freezing point	: No data available

9. Physical and chemical properties (continued)

Decomposition point [°C]	: No data available
Critical temperature [°C]	: No data available
Auto-ignition temperature [°C]	: No data available
Flammability (solid, gas)	: No data available
Flash point [°C]	: 35
Initial boiling point [°C]	: No data available
Final boiling point [°C]	: No data available
Evaporation rate	: No data available
Acid/alkali reserve [g NaOH/100g]	: No data available
Explosion limits - lower [%]	: No data available
Explosion limits - upper [%]	: No data available
Vapour pressure mm/Hg	: No data available
Vapour density	: No data available
Density [g/cm ³]	: 1.41-1.44
Solubility in water [% weight]	: No data available
Solubility in water	: Insoluble
Log Pow octanol / water at 20°C	: No data available
Solubility	: Organic solvents
Viscosity at 20°C [mPa.s]	: 1500-3000
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

10. Stability and reactivity

10.1. Reactivity

Reactivity : Not established.

10.2. Chemical stability

Chemical stability : Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions : Not established.

10.4. Conditions to avoid

Conditions to avoid : Open flame. Overheating. Direct sunlight. Heat. Sparks. Extremely high or low temperatures.

10.5. Incompatible materials

Materials to avoid : Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products : May release flammable gases. Fumes.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Harmful if inhaled
Corrosion	: Not established.
Irritation	: Causes serious eye irritation. Causes skin irritation.
Sensitization	: May cause an allergic skin reaction.
Mutagenicity	: Not established.
Carcinogenicity	: Not established.
Toxic for reproduction	: Not established.
STOT-single exposure	: Not established.
STOT-repeated exposure	: Not established.
Aspiration hazard	: Not established.

12. Ecological information

12.1. Toxicity

Toxicity information : The product has been not fully tested.
The calculated risk has been done under the requirements of the EU regulations.

12.2. Persistence - degradability

Persistence - degradability 12.3. : No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential : Not established.

12.4. Mobility in soil

Log Pow octanol / water at 20°C : No data available.

Mobility in soil : Not established.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment : Not applicable.

12.6. Other adverse effects

Environmental precautions : Avoid release to the environment.

13. Disposal considerations

13.1. Waste treatment methods

General : Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Avoid release to the environment.

Special precautions : Handle empty containers with care because residual vapours are flammable.

14. Transport information

14.1. Land transport (ADR-RID)

General information : NOT SUBJECT TO THE PROVISIONS OF ADR
- The product is packed in receptacles of less than 450 litres capacity
- Exempted according to 2.2.3.1.5 (Viscous substance exemption)

Proper shipping name : COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)

UN N° : 1139

H.I. nr : 30 : 3

ADR - Class : 3


ADR - Classification code : F1

ADR - Group : III

ADR - Packing instructions : P001 R001 LP001

ADR - Limited Quantity : 5 L

ADR - Tunnel code : D/E



14. Transport information (continued)

14.2. Sea transport (IMDG) [English only]

General information	: NOT SUBJECT TO THE PROVISIONS OF IMDG CODE FOR THE MARKING, LABELLING AND TESTING OF PACKAGES IN CHAPTERS 4.1, 5.2, AND 6.1. - The product is packed in receptacles not exceeding 30 L capacity - The following statement shall be included in the transport document: "Transport in accordance with 2.3.2.5 of the IMDG Code."
Proper Shipping Name	: COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)
UN N°	: 1139
IMO-IMDG - Class or division	: 3
IMO-IMDG - Packing group	: III
IMO-IMDG - Packing instructions	: P001 LP01
IMO-IMDG - Limited quantities	: 5 L
IMO-IMDG - Marine pollution	: No
EMS-Nr	: F-E S-E

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name	: COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)
UN N°	: 1139
IATA - Class or division	: 3
IATA - Packing group	: III
IATA - Passenger and Cargo Aircraft	: ALLOWED
- Passenger and Cargo - Packing instruction	: 355
- Passenger and Cargo - Maximum Quantity/Packing	: 60 L
IATA - Cargo only	: ALLOWED
- Cargo only - Packing instruction	: 366
- Cargo only - Maximum Quantity/	: 220 L
Packing	
IATA - Limited Quantities	: 10 L
ERG-Nr	: 3L

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental regulations/legislation specific for the substance or mixture	: Ensure all national/local regulations are observed.
REACH Restrictions - Annex XVII	: The components of this product are not subject to restrictions.
REACH Authorisation - Annex XIV	: The components of this product are not subject to authorization.

15.2. Chemical Safety Assessment

Chemical Safety Assessment	: It has not been carried out.
----------------------------	--------------------------------

16. Other information

Revision	: Revision - See : *
Abbreviations and acronyms	: PBT: persistent, bio accumulative and toxic. vPvB: very persistent and very bio accumulative
Sources of key data used	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
List of relevant R phrases (heading 3)	R10 : Flammable. R20/21 : Harmful by inhalation and in contact with skin. R36/37/38 : Irritating to eyes, respiratory system and skin. R43 : May cause sensitization by skin contact. R65 : Harmful : may cause lung damage if swallowed.
List of full text of H-statements in section 3	H226 : Flammable liquid and vapour. H304 : May be fatal if swallowed and enters airways. H312 : Harmful in contact with skin. H315 : Causes skin irritation. H317 : May cause an allergic skin reaction. H319 : Causes serious eye irritation. H332 : Harmful if inhaled. H335 : May cause respiratory irritation. H373 : May cause damage to organs through prolonged or repeated exposure.
Further information	: None.

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in anyway connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.



Harding Way, St Ives, Cambridgeshire, PE27 3YJ
Tel: 01480 466 777 Fax: 01480 290 133
Email: info@fix-r.co.uk Website: www.fix-r.co.uk