

STAIN BLOCKER PRIMER



For use with FIX-R Liquid Roofing System.

A high build, cost effective acrylic stain blocker for use on all bitumen based substrates.

Description

- A water based, high viscosity blue coloured primer.
- Intended for adhesion promotion and stain blocking on bitumen or asphalt substrates; also acts as a high build primer on those surfaces.
- All chippings or ballast must be removed from the substrate; the surface must be cleaned thoroughly by power washing and then sealed with FIX-R Stain Blocker Primer.

Application

- Surfaces must be clean and dry, free of dirt, dust, loose granules, pollution fallout or other contamination.
- Thoroughly mix containers to achieve an even consistency prior to use.
- Apply with brush or roller.
- Apply FIX-R Stain Blocker at the rate of approximately 0.3 to 0.5 L/m².
- Substrate porosity and texture will influence the coverage rate.
- Allow FIX-R Stain Blocker to dry thoroughly prior to applying FIX-R Liquid Roofing.

Typical Properties

Drying time 1 hour (at 20°C / 50% RH dependent on consumption rate).

Bucket Size

4 Litre plastic buckets.

Precautions

- FIX-R Stain Blocker Primer will freeze and become unusable at temperatures below 0°C.
- Do not apply if weather conditions will not allow the FIX-R Stain Blocker to dry before rain, dew or freezing temperatures occur.
- For additional information refer to the SDS.
- Avoid contact with eyes and mucous membranes.
- If material comes in direct contact with skin, wash immediately with soap and water.

Safety & Handling

For specific information regarding safe handling of this material please refer to the Safety Data Sheet (SDS).

Date of issue: Feb 20