

GP PRIMER



For use with FIX-R Liquid Roofing System.

A water based, low viscosity white primer intended for adhesion promotion on various substrates.

Intended Use

FIX-R Liquid Roofing GP Primer is designed to improve adhesion to the following substrates:

- PVC Single Ply Membrane
- Treated and Untreated Wood
- GRP
- Approved Insulation Boards
- OSB3 Decking Boards

Application

- Ensure the substrate is sound, clean, dry and free of frost, dust and debris, and any material which would hinder adhesion.
- Stir opened primer to ensure uniform material consistency.
- Apply with brush or roller.
- Apply FIX-R GP Primer at the rate of approximately 0.1 - 0.2 L/m².

Typical Properties

Drying time 1 hour

Precautions

- FIX-R GP Primer will freeze and become unusable at temperatures below 0°C.
- Do not apply if weather conditions will not allow the FIX-R GP Primer to dry before rain, dew or freezing temperatures occur.

Safety & Handling

For specific information regarding safe handling of this material please refer to the Safety Data Sheet (SDS).

Apply only when atmospheric and substrate temperatures are greater than 5°C. The surface of the substrate should be clean and dry and must be 3°C above the dew point. If the surface is below or at dew point temperature then moisture can form at the surface and affect coating adhesion and curing.

- Substrate porosity and texture will influence the coverage rate.
- FIX-R Liquid Roofing can be applied above the primed surface when the white Primer coating cures to form a dry, transparent film finish. Depending upon atmospheric conditions, curing time can be 20 minutes (at 20°C / 50% RH).

Bucket Size

4 Litre plastic buckets.

- For additional information refer to the SDS.
- Avoid contact with eyes and mucous membranes.
- If material comes in direct contact with skin, wash immediately with soap and water.

Date of issue: Feb 20